

THOR PC 20 & 24

FEATURES

- Modern design with robust construction and innovative controls
- Used in conjunction with hook-lift loading systems
- Available in 18, 20, and 24m³ containers
- Fully sealed doors as standard
- Various loading options and lifting devices available to cater for 110L to 1100L wheeled DIN Containers



SPECIFICATION	THOR PC 20 Three Phase	THOR PC 20 Single Phase	THOR PC 24 Three Phase	THOR PC 24 Single Phase
Motor size	4 kw	2.2 kw	5.5 kw	2.2 kw
Compaction force	28 tonne	24 tonne	28 tonne	24 tonne
Operating pressure	160 bar	165 bar	160 bar	165 bar
Cycle time	67 seconds	76 seconds	68 seconds	90 seconds
Charge box volume	1.51 m ³	1.51 m ³	2.22 m ³	2.22 m ³
Volume per stroke	.99 m ³	.99 m ³	1.49 m ³	1.49 m ³
Max. Throughput per hour	54 m ³	47 m ³	80 m ³	60 m ³
Ram penetration	250 mm	250 mm	440 mm	440 mm

SPECIFICATION	THOR PC 20 / 18	THOR PC 20 / 20	THOR PC 20 / 24	THOR PC 24 / 18	THOR PC 24 / 20
Compactor width	2500	2500	2500	2500	2500
Compactor height	2550	2550	2550	2550	2550
Compactor length	5955	6270	6585	6325	6950
Loading height	1430/1200	1430/1200	1430/1200	1430/1200	1430/1200
Charge box length	1000	1000	1000	1500	1500
Charge box depth	1150	1150	1150	1150	1150
Charge box width	1800	1800	1800	1800	1800
Total volume	18 m ³	20 m ³	24 m ³	18 m ³	20 m ³
Weight	4025 kg	4150 kg	4300 kg	4275 kg	4400 kg